

SAFETY DATA SHEET

Page: 1 of 5
Process Time: 8:43 am

Date Revised: 5/18/18

Date Printed: 12/6/18

SECTION 1 - IDENTIFICATION

MANUFACTURER: BURKE INDUSTRIAL COATINGS EMERGENCY PHONE: 1-800-424-9300
ADDRESS : 11400 WEST 47TH STREET INFORMATION PHONE: (952)938-7223
MINNETONKA, MN 55343 NAME OF PREPARER : Safety Director

PRODUCT NAME: PRIME SOLUTION 5253 GREY

PRODUCT CODE: BIC-30-5253

SECTION 2 - HAZARDS IDENTIFICATION

HAZARD RISK CLASSIFICATION

SIGNAL WORD: WARNING

PICTOGRAM:

GHS07 - EXCLAMATION MARK GHS08 - HEALTH HAZARD

HAZARD CLASS

HAZARD CATEGORY

ACUTE TOXICITY

CATEGORY 4 INHALATION

SKIN CORROSION /IRRITATION

CATEGORY 2

SERIOUS EYE DAMAGE /

CATEGORY 2 AND 2A

EYE IRRITATION

CARCINOGENICITY

CATEGORY 2

TOXIC TO SPECIFIC TARGET ORGAN

CATEGORY 3

TOXICITY - SINGLE EXPOSURE

HAZARD STATEMENTS:

H303 May be harmful if swallowed

H315 Causes skin irritation

H319 Causes serious eye irritation.

H332 Harmful if inhaled

H335 May cause respiratory irritation

H351 Suspected of causing cancer.

Chemical(s) which may be considered a cancer hazard by IARC and/or NTP.

Refer to section 11 for further information.

PRECAUTIONARY STATEMENTS:

PREVENTION:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/hot surfaces/sparks/open flames and other sources of ignition. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilation/lighting/handling equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapor/ spray.

P264 Wash hands and any exposed area thoroughly after handling.

P271 Use only outdoors or in well-ventilated area.

P281 Use appropriate personal protective impervious gloves/protective clothing/ OSHA approved eye protection/ face protection.

RESPONSE:

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated

SAFETY DATA SHEET

Date Revised: 5/18/18

Date Printed: 12/6/18

clothing. Rinse skin with water (or shower).
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 If exposed or concerned: Get medical advice / attention.
P312 Call a POISON CENTER/doctor if you feel unwell.
P321 Specific treatment (see on this label)
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use carbon dioxide (CO2), powder, alcohol-resistant foam to extinguish.

STORAGE:
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

DISPOSAL:
P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

===== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS =====

COMPONENT	CAS NUMBER	WEIGHT PERCENT	EXPOSURE LIMITS		
			OSHA PEL	ACGIH TLV	OTHER
TALC	14807-96-6	1-10			
Titanium Dioxide	13463-67-7	1-10			
			10 mg/m3	10 mg/m3	
Propylene Glycol N-Butyl Ether	5131-66-8	1-10			
			NOT ESTABLISHED		
# Carbon Black	1333-86-4	.2			
			3.5 MG/M3	3.5 MG/M3	

* Chemical(s) that are chronic health hazards. Refer to section 3 for further information.

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation. **INHALATION:** Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.

CHRONIC HEALTH EFFECTS:

Although some components may indicate chronic exposure effects, no effects are anticipated under normal use conditions due to the relatively low proportion in the total mixture.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

===== SECTION 4 - FIRST AID MEASURES =====

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

SAFETY DATA SHEET

Page: 3 of 5
Process Time: 8:43 am

Date Revised: 5/18/18

Date Printed: 12/6/18

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Greater than 200 F

METHOD USED: SETAF flash

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1

UPPER: 8.4

EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION:

General room ventilation is adequate.

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: Various colors

ODOR: Amine or ammonia odor

SOLUBILITY IN WATER: Dilutable

SPECIFIC GRAVITY (H2O=1): 1.24

VAPOR DENSITY: Heavier than air.

BOILING RANGE:

EVAPORATION RATE: Slower than nBuAc

SAFETY DATA SHEET

Page: 4 of 5
Process Time: 8:43 am

Date Revised: 5/18/18

Date Printed: 12/6/18

COATING V.O.C.: 362 g/l (3.02 lb/gal)

SECTION 10 - STABILITY AND REACTIVITY DATA

STABILITY:

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (MATERIALS TO AVOID):

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

SENSITIZATION:

None known.

CARCINOGENICITY:

The indicated chemical(s) is listed by ICGIH, NTP, or OSHA as a known human carcinogen (See section 2). IARC concluded that there is "sufficient evidence in experimental animals for the carcinogenicity of carbon black" and inadequate evidence of carcinogenicity in humans, and overall evaluated carbon black as a "possible carcinogen to humans" (Group 2B). Carbon black has not been listed as a carcinogen by NTP or OSHA. Because this product is a free flowing liquid, inhalation is not an expected route of exposure.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

SECTION 12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA:

No known effects or critical hazards. No data available.

SECTION 13 - DISPOSAL CONSIDERATIONS

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

SHIPPING NAME:

Not regulated.

SECTION 15 - REGULATORY INFORMATION

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

STATE LISTED COMPONENTS	CAS NUMBER	STATE CODE
-------------------------	------------	------------

CALIFORNIA PROPOSITION 65

This product contains a chemical(s) known to the state of California to cause cancer, birth defects or reproductive harm, which are subject to the requirements of California Proposition 65.

SECTION 16 - OTHER INFORMATION

SAFETY DATA SHEET

Page: 5 of 5
Process Time: 8:43 am

Date Revised: 5/18/18

Date Printed: 12/6/18

REVISION DATE: 05/18/18

HMIS CODES: H	F	R	P
1	0	0	B