

Positest® DFT
Coating Thickness Gage

Conforms to: ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D1400/E276/G12, BS3900-C5, SSPC-PA2 and others. Certificate of Calibration traceable to NIST available.

Two Models:

PosiTest DFT Ferrous measures non-magnetic coatings on steel.

PosiTest DFT Combo measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. Automatically recognizes the substrate and takes a measurement.

Ideal for:

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

Features:

- Flip display for right side up viewing
- Built-in wrist strap
- Fast, repeatable measurements
- No calibration required for most applications
- Zero feature for rough or curved surfaces
- Handy Reset feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mils/Microns switchable
- Basic instructions on the back of each gage



Gage comes complete with built-in probe, plastic shims, hard shell storage case, AAA battery, instructions and a one (1) year warranty.

Specifications:

Measurement Range	0-40 mils	0-1000µm
Accuracy	±(0.1 mils + 3%)	±(2µm + 3%)
Size	4 x 1.5 x 0.9 in.	100 x 38 x 23 mm.
Weight	2.5 oz.	70 g.