SAFETY DATA SHEET

Page: 1 of 5
Process Time: 12:05 pm

Date Revised: 5/1/23 Date Printed: 6/13/23

PRODUCT NAME: PRIME SOLUTION 5253GREY (ALT RESIN)

PRODUCT CODE: BIC-30-5253 XEA171

RECOMMENDED USE: PAINT OR PAINT RELATED MATERIAL

MANUFACTURER: BURKE INDUSTRIAL COATINGS ADDRESS: 11400 WEST 47TH STREET

MINNETONKA, MN 55343 USA

TELEPHONE: 952-938-7223 E-mail: safety@fenixspc.com

24 HOUR EMERGENCY PHONE: CHEMTREC 1-800-424-9300

HAZARD RISK CLASSIFICATION

SIGNAL WORD: WARNING

PICTOGRAM:

GHS07 - EXCLAMATION MARK

HAZARD CLASS

HAZARD CATEGORY

ACUTE TOXICITY CATEGORY 4 INHALATION

SKIN CORROSION / IRRITATION CATEGORY 2

SERIOUS EYE DAMAGE / CATEGORY 2 AND 2A

EYE IRRITATION

TOXIC TO SPECIFIC TARGET ORGAN CATEGORY 3

TOXICITY - SINGLE EXPOSURE

HAZARD STATEMENTS:

Н303	May be harmful if swallowed
Н315	Causes skin irritation
Н319	Causes serious eye irritation.
Н332	Harmful if inhaled
Н335	May cause respiratory irritation

PRECAUTIONARY STATEMENTS:

PREVENTION:

P210 Keep away from heat/hot surfaces/sparks/open flames and other

sources of ignition. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilation/lighting/handling

equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapor/ spray.

P264 Wash hands and any exposed area thoroughly after handling.

P271 Use only outdoors or in well-ventilated area.

P280 Wear protective impervious gloves/ OSHA approved eye

protection/face protection.

RESPONSE:

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for

breathing.

SAFETY DATA SHEET

Page: 2 of 5 Process Time: 12:05 pm

Date Revised: 5/1/23 Date Printed: 6/13/23

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label)

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use carbon dioxide (CO2), powder, alcohol-

resistant foam to extinguish.

STORAGE:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

DISPOSAL:

P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

OTHER HAZARDS: NONE KNOWN

HMIS RATING: H F R PPE

1 0 0 E

======== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS ==========

		WEIGHT		EXPOSURE LIMITS	
COMPONENT	CAS NUMBER	PERCENT	OSHA PEL ACGIH	TLV OTHER	
Talc	14807-96-6	7.5-10.0			
			2 MG/M3	2 MG/M3	
Titanium Dioxide	13463-67-7	7.5-10.0			
			10 mg/m3	10 mg/m3	
Propylene Glycol N-Butyl Ether	5131-66-8	0-2.5			
			NOT ESTA	NOT ESTABLISHED	

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

DESCRIPTION OF FIRST AID MEASURES:

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: If a large amount is ingested, give water or milk and induce vomitting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

EYES: Direct contact with eyes may cause irritation.

SKIN: Prolonged or repeated contact may cause irritation.

INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

SAFETY DATA SHEET

Page: 3 of 5 Process Time: 12:05 pm

Date Revised: 5/1/23

Date Printed: 6/13/23

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.

CHRONIC HEALTH EFFECTS:

No anticipated chronic effects.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Treat symptomatically.

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIFIC HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

In the event of fire, harmful vapors including carbone monoxide, carbond dioxide, and others may be released. There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Evacuate area and keep unnecessary and

unprotected personnell from entering the spill area. Use proper personal protective equipment listed in section 8.

ENVIRONMENTAL PRECAUTIONS: Keep runoff from storm sewars, ditches, streams, lakes and other ground waters and waterways. May be toxic to aquatic life.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:

Contain all spills. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Collect into suitable containers and dispose of properly in accordance with all applicable regulations. (See Section 13) Rinse affected area thoroughly with water.

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communicatin Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

PRECAUTIONS FOR SAFE STORAGE:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

ENGINEERING CONTROLS: General room ventilation is adequate.

PERSONAL PROTECIVE EQUIPMENT:

RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

Page: 4 of 5 Process Time: 12:05 pm

Date Revised: 5/1/23 Date Printed: 6/13/23

PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

======== SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ===========

APPEARANCE/PHYSICAL STATE: Liquid
ODOR: Amine or ammonia odor

ODOR THRESHOLD: Not measured

MELTING/FREEZING POINT: Not Determined SPECIFIC GRAVITY (H2O=1): 1.22

EVAPORATION RATE: Not Determined

FLASH POINT: Greater than 200 FSETAFLASH

UPPER EXPLOSION LIMIT: 8.4
LOWER EXPLOSION LIMIT: 1.1

DECOPMPOSITION TEMPERATURE: Not Available

COATING V.O.C.: 308 g/l (2.57 lb/gl)

COLOR: Various colors

pH: Not Determined

SOLUBILITY IN WATER: Dilutable

BOILING POINT/RANGE:

VAPOR DENSITY: Greater Than Air FLAMMABILITY: Not determined VAPOR PRESSURE: Not Determined

AUTO-IGNITION TEMPERATURE: Not Determined
PARTITION COEFFICIENT: Not Available

VISCOSITY: Not Determined

REACTIVITY: Will not occur.

CHEMICAL STABILITY:

Stable under normal conditions and handling.

POSSIBILITY OF HAZARDOUS REACTIONS:

No hazardous reactions if stored and handled as prescribed/indicated.

CONDITIONS TO AVOID:

None known

INCOMPATIBLE MATERIALS:

None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

SENSITIZATION:

None known.

CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

REPRODUCTIVE TOXICITY:

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

ECOTOXICITY:

No data available.

Page: 5 of 5 Process Time: 12:05 pm

Date Revised: 5/1/23

Date Printed: 6/13/23

PERSISTENCE AND DEGRADABILITY:

Not readily degradable.

BIOACCUMULATIVE POTENTIAL:

No data available.

MOBILITY IN SOIL:

No data available.

OTHER ADVERSE EFFECTS: No known effects or critical hazards. No data available.

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

PROPER SHIPPING NAME: (UN #, SHIPPING NAME, HAZARD CLASS, PACKING GROUP)

Not regulated.

US TOXIC SUBSTANCE CONTROL ACT (TSCA):

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

SARA 302 EXTREMELY HAZARDOUS SUBSTANCE: None

SARA 311/312 HAZARDOUS CHEMICAL: See Section 3

SARA 313 (TRI REPORTING):

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

STATE LISTED COMPONENTS CAS NUMBER STATE CODE

CALIFORNIA PROPOSITION 65

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

REVISION DATE: 05/01/23

This version repaces all previous versions. The information contained in this SDS and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Although certain hazards are described herin, The Sierra Company, LLC, cannot guarantee that tehse are the only hazards that exist. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall The Sierra Company, LLC, assume liability for damages or losses of any kind or nature that result from the use of or relieance upon this information and recommendations. The Sierra Company, LLC, experessly disclaims any represtentations and warranties of any kind, whether express or implied, as to the accuracy, completeness, non-infringment, merchantability and/or fitness for a particular purpose with respect to any information and recommendations provided. The Sierra Company, LLC, reserves the right to make any changes to the information and/or recommendations at any time, without prior subsequent notice.